



DATE: 6 February, 2017

PCN #: 2257

PCN Title: Datasheet Change for High Level Gate Driver Output Voltage Minimum and Typical Values on Select Analog Parts

Dear Customer:

This is an announcement of change(s) to products that are currently being offered by Diodes Incorporated.

We request that you acknowledge receipt of this notification within 30 days of the date of this PCN. If you require samples for evaluation purposes, please make a request within 30 days as well. Otherwise, samples may not be built prior to this change. Please refer to the implementation date of this change as it is stated in the attached PCN form. Please contact your local Diodes sales representative to acknowledge receipt of this PCN and for any sample requests.

The changes announced in this PCN will not be implemented earlier than 90 days from the notification date stated in the attached PCN form.

Previously agreed upon customer specific change process requirements or device specific requirements will be addressed separately.

For questions or clarification regarding this PCN, please contact your local Diodes sales representative.

Sincerely,

Diodes Incorporated PCN Team



PRODUCT CHANGE NOTICE**PCN-2257 REV 00**

Notification Date:	Implementation Date:	Product Family:	Change Type:	PCN #:
6 February, 2017	6 May, 2017	Analog	Datasheet change	2257
TITLE				
Datasheet Change for High Level Gate Driver Output Voltage Minimum and Typical Values on Select Analog Parts				
DESCRIPTION OF CHANGE				
This PCN is being issued to notify customers that there will be changes to the datasheet as described in the Figures below. Please contact your local Diodes representatives for any questions or additional information.				
IMPACT				
Figure 1: Current Datasheet – Electrical Characteristics for ZXLD1370EST16TC Figure 2: Updated Datasheet - Electrical Characteristics for ZXLD1370EST16TC Figure 3: Current Datasheet – Electrical Conditions for ZXLD1371EST16TC Figure 4: Updated Datasheet – Electrical Conditions for ZXLD1371EST16TC There will be no change to the Form or Fit of affected products.				
PRODUCTS AFFECTED				
ZXLD1370EST16TC, ZXLD1371EST16TC				
WEB LINKS				
Manufacturer's Notice:	http://www.diodes.com/pcns			
For More Information Contact:	http://www.diodes.com/contacts.html			
Data Sheet:	http://www.diodes.com/catalog			
DISCLAIMER				
Unless a Diodes Incorporated Sales representative is contacted in writing within 30 days of the posting of this notice, all changes described in this announcement are considered approved.				

Figure 1: Current Datasheet – Electrical Characteristics for ZXLD1370EST16TC

Electrical Characteristics (cont.) ($V_{IN} = V_{AUX} = 12V$, $T_A = +25^\circ C$, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Driver output (PIN GATE)						
V _{GATEH}	High level output voltage	No load Sourcing 1mA (Note 14)	10	11		V

Figure 2: Updated Datasheet - Electrical Characteristics for ZXLD1370EST16TC

Symbol	Parameter	Conditions	Min	Typ	Max	Units
V _{GATEH}	High Level Output Voltage	No Load Sourcing 1mA (Note 15)	$V_{IN} = V_{AUX} = 12V$ 9.5	10.5	—	V
			$V_{IN} = V_{AUX} = 6.5V$ 4	5		

Figure 3: Current Datasheet – Electrical Characteristics for ZXLD1371EST16TC

Electrical Characteristics (cont.) (Test conditions: $V_{IN} = V_{AUX} = 12V$, $T_A = 25^\circ C$, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Driver output (PIN GATE)						
V _{GATEH}	High level output voltage	No load Sourcing 1mA (Note 12)	10	11		V

Figure 4: Updated Datasheet – Electrical Characteristics for ZXLD1371EST16TC

Symbol	Parameter	Conditions	Min	Typ	Max	Units
Driver output (PIN GATE)						
V _{GATEH}	High-level output voltage	No load Sourcing 1mA (Note 14)	$V_{IN} = V_{AUX} = 12V$ 9.5	10.5	-	V