

Home > [Products](#) > [Clock / Timing Devices](#) > [PC-Notebook-Server Clocks](#) > [Clock Synthesizer by Chipset Vendor](#) > [Notebook Chipsets](#) > [9LPR600](#) > 9LPR600CGLF

You may also like...



## 9LPR600CGLF

**Category:** Notebook Chipsets  
**Generic Part:** 9LPR600  
**Market Group:** PC CLOCK  
**Description:** SIS 662 MAIN CLOCK  
 Low Power Main Clock for SiS 662 style chipset

### Output Features:

- 1 - pair of differential push-pull CPU outputs
- 1 - pair of differential push-pull CPU outputs, free-running
- 4 - 0.7V differential PCIEX pairs
- 2 - 0.7V differential PCIEX\_F pairs, free-running
- 1 - 0.7V differential SATA pair
- 6 - PCI (33MHz)
- 2 - PCI (33MHz), free-running
- 1 - 24/48MHz selectable output
- 2 - ZCLK
- 2 - REF, 14.318MHz
- 1 - 12MHz output

### Parameters

Temperature	C
Voltage	3.3 V
Package	TSSOP 56
Speed	NA
Status	Active
Sample	Yes
Minimum Order Quantity	102
Factory Order Increment	34

### Distributor Inventory

No Pricing information is available from our Distributors at this time.

### Documents

Type	Title	Size	Revision Date
Datasheet	954201 Datasheet	163 KB	03/27/2006
	954204 Datasheet	200 KB	03/27/2006
	954321 Datasheet	225 KB	03/27/2006
Misc	PC Clocks Contact Info	61 KB	05/29/2007

### Package

Package	TSSOP 56 (PAG56)
Description	TSSOP 6.1 MM 0.5MM PITCH
Status	Active
Class	PLASTIC
Category	Green
Pb (Lead) Free	Yes
Mark	G
Package Type	TSSOP
Lead Count	56
Length	14.0 mm
Width	6.1 mm
Thickness	1.0 mm
Pitch	0.5 mm
Tube / Tray	TUBE
Quantity per Tube/Tray	34
Quantity per Reel	1000
Moisture Sensitivity Level (MSL)	1
Moisture Exposure Floor Life	Unlimited@<30C/85%RH
Peak Reflow Temperature	260Å°C
Rebake Conditions	NA
Related Package Documents	<a href="#">view documents</a>